Datasheet Conveyor Belt



Berenkoog 25 1822 BH Alkmaar The Netherlands

T: +31 (0)72 562 22 34 F: +31 (0)72 561 32 38


E: sales@nitta.nl www.nittacorporation.com

• NITTA BELT TYPE:

3 CF

Nitta Japan code:

CC-18DKC



Construction: 3 plies cotton/polyester, non-rigid

TOP COVER INNER LAYER BOTTOM SIDE

Material: Cotton fabric PVC Cotton/polyester

fabric

Thickness: - mm (approx.)

Colour: - White -

Total thickness: 3,1 mm (approx.)
Weight: 3,4 kg/m² (approx.)

Max. width: 2000 mm

Belt support: Sliderbed (Rollers), Flat/trough

Rating at 1% elongation: 12 N/mm
Advised pretension: 4 - 7 N/mm
Maximum allowable tension: 20 N/mm
Temperature range: -10 to +90 °C

Minimum pulley diameters:

Flexing: 80 mm
Backflexing: 80 mm

Special approval: FDA, 10/2011/EC + amendments

Applications: Conveying of (un)vulcanised rubber

Excellent release of dough in bakeries

Conveyor belt in bakeries

Accumulation belt

Date of issue 19-06-2014-1